

L Series Recovery Unit



Light • Fast

One Key Operation

- Easy to use

Self-purge Function

- Prevent mixing of various refrigerants

Oil-free Compressor

- Suitable for all commonly used refrigerants

High Pressure Protection

- Safe to use

Model		VRR12L			VRR12L-OS				
Refrigerant		Categories III : R12, R134a, R401C, R500 Categories IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categories V : R402A, R404A, R407A, R407B, R410A, R507							
Power Supply		220-240V~/50-60Hz		115V~/60Hz		220V-240V~/50-60Hz		115V~/60Hz	
Motor		3/4 HP		3/4 HP		3/4 HP		3/4 HP	
Motor Speed		1450 rpm/1750 rpm		1750 rpm		1450 rpm/1750 rpm		1750 rpm	
Maximal Current Draw		4 A		8 A		4 A		8 A	
Compressor		Oil-less, Air-cooled, Piston style							
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)							
Recovery Rate (kg/min)		Categories III	Categories IV	Categories V	Categories III	Categories IV	Categories V		
	Vapor	0.20	0.25	0.25	0.20	0.25	0.25		
	Liquid	1.60	1.80	2.20	1.60	1.80	2.20		
	Push/Pull	4.60	5.60	6.30	4.60	5.60	6.30		
Operating Temperature		0°C-40°C							
Dimensions		400×250×355 mm							
Weight		13.0 kg			14.2 kg				